



# **EZ2003 Total Manganese Analyser**

Proizvod #: EZ2003.XXXXXXXX

EUR Cijena: Kontaktirajte nas

## Online colorimetric analysis of Total Manganese in water

EZ2000 Total Manganese Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low µg/L range.

EZ2000 Total Manganese Analysers have an internal digestion unit. This additional step prior to analysis allows to measure non-soluble or complexed metal species.

### Results you can rely on

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator invervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

# Flexibility that meets your needs

EZ Series Total Manganese Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

### Specifikacije

Alarma: 1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts

Analogni izlazi: Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)

Broj uzoraka: 1, 2, 4 or 8

Certificiranja: CE compliant / UL certified

Demineralised water: For rinsing / dilution

Digital outputs: Optional: Modbus (TCP/IP, RS485)

Dimenzije (V x Š x D): 690 mm x 465 mm x 330 mm

Earth connection: Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm<sup>2</sup>

Garancija: 24 mjeseci

Granica detekcije:  $\leq 4 \mu g/L$ 

Instrument air: Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air

Interferencija: Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar.

Kalibracija: Automatic, 2-point; frequency freely programmable

Kivete: 20 min Total Mn (dilution + 5 min)

30 min Total Mn & Mn (II)

Klasa zaštite: Protection class: Analyser cabinet: IP44 / Panel PC: IP65

Kvaliteta uzorka: Maximum particle size 100  $\mu$ m, < 0.1 g/L; Turbidity < 50 NTU

Masa: 25 kg

Materijal: Hinged part: Thermoform ABS, door: PMMA

Wall section: Galvanised steel, powder coated

Mjerna metoda: Colorimetric measurement using formaldoxime method at 450 nm

Mjerni rang: 0.02 - 1 mg/L Mn

Optional:

0.004 - 0.1 mg/L

0.01 - 0.25 mg/L

0.01 -  $0.5\ mg/L$ 

0.16 - 4 mg/L (with internal dilution)

0.32 - 10 mg/L (with internal dilution)

2 - 20 mg/L (with internal dilution)

Napajanje: 230 VAC, 50/60 Hz

120 VAC, 50/60 Hz

Max. power consumption: 440 VA

Odvod: Atmospheric pressure, vented, min. Ø 32 mm

Parametar: Manganese, total

Precision: Better than 2% full scale range for standard test solutions

Protok uzorka: 100 - 300 mL/min

Reagent Requirements: Keep between 10 - 30 °C

Što je u pretincu: EZ2003 Manganese Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting

Brackets, 4 x empty 2.5L Reagent Containers with Fittings (for Acid, Reductor, Buffer, Colour & Mixed Reagent Solution) and 1 x empty 10L Reagent Container with Fittings (for EDTA

Solution)

Temperatura prostora: 10 - 30 °C ± 4 °C deviation at 5 - 95% relative humidity (non-condensing)

Temperatura uzorka: 10 - 30 °C

Uzorak: tlak: By external overflow vessel

Validation: Automatic; frequency freely programmable

# Što je u pretincu EZ2003 Manganese Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 4 x empty 2.5L Reagent Containers with Fittings (for Acid, Reductor, Buffer, Colour & Mixed Reagent Solution) and 1 x empty 10L Reagent Container with Fittings (for EDTA Solution)