



Polymetron 8398.5 Inductive conductivity sensor, 1" thread

Proizvod #: 08398=A=5000
EUR Cijena: Kontaktirajte nas
Otprema unutar 2 tjedna

Immersion probe for conductivity measurements also under harsh conditions. Polyetheretherketone (PEEK) body, 5m cable, runs with several types of controllers. In-built temperature element.

High chemical and mechanical resistance

Accuracy over a wide measuring range

For some types: perfect compact sanitary design for 2"/DN50 access port in compliance with 3A standards

Maintenance free: No electrode damage, no polarisation effect

Versatile mounting options: flow-through adapters and chambers, immersion shafts

Specifikacije

Duljina kabla:	5 m fixed cable
Konstanta k kivete:	2.35
Masa:	0,700 kg
Materijal:	Gasket: EPDM; PEEK
Materijali u dodiru s vodom:	PEEK
Mjerni rang:	0,2 - 2000 mS/cm
Mjerno načelo:	Inductive conductivity measurement
Navoj senzora:	1" outer thread for immersion applications
Ponovljivost:	< ± 2 % ili ± 0,004 mS/cm, koje je od toga veće
Radna temperatura:	140 °C maximum
Rang tlaka:	Max. 18 bar

Potrebni dodaci

- Kontroler SC4500, Prognosys, 5x mA izlaz, 2 digitalna senzora, 100 - 240 VAC, bez kabela napajanja (Item LXV525.99A11551)
- Kontroler SC4500, omogućen sustav Claros, 5x mA izlaz, 2 digitalna senzora, 100 - 240 VAC, bez kabela napajanja (Item LXV525.99AA1551)
- Kontroler SC4500, omogućen sustav Claros, 5x mA izlaz, 2 digitalna senzora, 100 - 240 VAC, EU utikač (Item LXV525.99CA1551)
- Kontroler SC4500, Prognosys, 5x mA izlaz, 1 digitalni senzor, 100 - 240 VAC, bez kabela napajanja (Item LXV525.99A11501)

- Kontroler SC4500, Prognosys, 5x mA izlaz, 2 digitalna senzora, 24 VDC, bez utikača (Item LXV525.99Z11551)