



EZ7861 Total Phosphorus/Orthophosphate Analyser, 0.005-1 mg/L TP/PO₄-P

Proizvod #: EZ7861.XXXXXXXXXX

EUR Cijena: Kontaktirajte nas

Nije prikazan datum isporuke

The full picture of Phosphorus removal: Total Phosphorus and Orthophosphate

You spend a lot of time looking at your data and your process, so you never come close to any compliance issues while managing your environmental and regulatory goals. When you choose the new EZ Series Total Phosphorus and Orthophosphate analyser from Hach, you'll get industry-leading technology with the power to measure both parameters in one analyser for a full picture of your Phosphorus removal process. Full process insight gives you the confidence to take action.

There are many additional instrument options available. Please contact Hach for more details.

Stay in control

Monitor your Phosphorus removal process with the reliable data and insights you need to act quickly and with confidence. Phosphorus discharge permits evolve, and the EZ Series Total Phosphorus and Orthophosphate analyser helps you quickly and accurately get both measurements to ensure permit compliance.

See the total picture

Be confident in your process. You employ biological treatment and/or chemical precipitation to remove Phosphate, but the ratio of effluent TP vs. ortho-PO₄ may vary throughout the day. The new TP/PO₄ analyser will get you actionable data for both parameters with one device. Continuous monitoring will enable you to detect trends. You'll always see both forms of Phosphorus in your water.

This isn't simple, but we'll help you simplify

Sampling for lab analysis can be time-consuming, costly, and incurs a delay, whereas continuous monitoring helps you to understand the process conditions much faster. The new combined analyser will make your day easier with features that help you save hands-on time. Cooling water is no longer needed. You'll enjoy the autocalibration, self-cleaning and automatic validation this analyser provides. Ready to use reagents and the unparalleled Hach service and support are there to help you optimise your work.

Specifikacije

| | |
|------------------------|---|
| Alarma: | 1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts |
| Analogni izlazi: | Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option) |
| Broj uzoraka: | 1, 2, 4, or 8 |
| Certificiranja: | CE compliant / ETL certified |
| Demineralised water: | For rinsing / dilution |
| Digital outputs: | Optional: Modbus (TCP/IP, RS485) |
| Dimenzije (V x Š x D): | 690 mm x 465 mm x 330 mm |
| Earth connection: | Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm ² |
| Garancija: | 24 mjeseci |

| | |
|-----------------------|--|
| Granica detekcije: | ≤ 0.005 mg/L |
| Instrument air: | Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air |
| Interferencija : | Arsenic (V), Chromium (VI), Copper (II) > 10 mg/L, Iron (III) > 10 mg/L, Sulphide > 2 mg/L, and Vanadium (V), Silica > 60 mg/L. Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar. |
| Kalibracija: | Automatic, 2-point; frequency freely programmable |
| Kivete: | Standard measurement cycle time for TP & Orthophosphate: 30 minutes |
| Klasa zaštite: | Analyser cabinet: IP44 / Panel PC: IP65 |
| Kvaliteta uzorka: | Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU |
| Masa: | 25 kg |
| Materijal: | Hinged part: Thermoform ABS, door: PMMA |
| | Wall section: Galvanised steel, powder coated |
| Mjerna metoda: | Colorimetric measurement at 700 nm using ascorbic acid reduction and molybdate colour solution after persulphate digestion in acidic medium, conform with APHA 4500-P |
| Mjerni rang: | 0.005 - 1 mg/L TP/PO ₄ -P |
| Napajanje: | 230 VAC, 50/60 Hz |
| | 120 VAC, 50/60 Hz |
| | Max. power consumption: 440 VA |
| Odvod: | Atmospheric pressure, vented, min. Ø 32 mm |
| Parametar: | Total Phosphorus (TP), Orthophosphate (PO ₄ -P) |
| Precision: | Better than 2% full scale range for standard test solutions |
| Protok uzorka: | 100 - 300 mL/min |
| Reagent Requirements: | Keep between 10 - 30 °C |
| Što je u pretincu: | EZ7861 Total Phosphorus/Orthophosphate Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets and empty Containers for Reagents with Fittings |
| Temperatura prostora: | 10 - 30 °C, ± 4 °C deviation at 5 - 95% relative humidity (non-condensing) |
| Temperatura uzorka: | 10 - 30 °C |
| Uzorak: tlak: | By external overflow vessel |
| Validation: | Automatic; frequency freely programmable |

Što je u pretincu

EZ7861 Total Phosphorus/Orthophosphate Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets and empty Containers for Reagents with Fittings