



## **EZ1032 Phosphate Analyser (Molybdate Blue Method) PO<sub>4</sub>-P**

**Proizvod #:** EZ1032.XXXXXXXXXX

EUR Cijena: Kontaktirajte nas

### **Online colorimetric analysis of Phosphate in water (Molybdate Blue Method)**

EZ1000 Phosphate Analysers achieve excellent precision and accuracy. At the heart of the colorimeter there is a compact photometer assembly developed especially for the EZ Series. Consumption of reagents is reduced by low volume analysis, yet high sensitivity is assured by a long optical path length. The limit of detection is in the low µg/L range.

#### **Results you can rely on**

Smart automatic features for calibration, validation, priming and cleaning are embedded in the controller software and contribute to analytical performance, maximised uptime and negligible operator intervention. Precision micropumps dose all reagents. Sample lines and analysis vessel are cleaned with demineralised water to eliminate cross contamination between samples. Electronic and wet-chemical part of the analyser are strictly separated. A transparent door allows for instant visual inspection of the wet part.

#### **Flexibility that meets your needs**

EZ Series Phosphate Analysers come in an attractive, ergonomic mainframe with a compact footprint. All hardware is controlled by the integrated industrial panel PC. The modular build allows for the analyser to match your application and operational needs.

- The standard measuring range can be narrowed by a different calibration range or extended via internal dilution options.
- Analogue and digital output options
- Multiple stream analysis for up to 8 sample streams

There are many additional options available. Please contact Hach for more details.

---

### **Specifikacije**

Alarma:	1 x malfunctioning, 4 x user-configurable, max. 24 VDC/0.5 A, potential free contacts
Analogni izlazi:	Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option)
Automatsko čišćenje:	Da
Broj uzoraka:	1, 2, 4, or 8
Certificiranja:	CE compliant / ETL certified
Demineralised water:	For rinsing / dilution
Digital outputs:	Optional: Modbus (TCP/IP, RS485)
Dimenzije (V x Š x D):	690 mm x 465 mm x 330 mm

Earth connection:	Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm <sup>2</sup>
Garancija:	24 mjeseci
Granica detekcije:	≤ 1 µg/L
Instrument air:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air
Interferencija :	Arsenic (V), Chromium (VI), Copper (II) > 10 mg/L, Iron (III) > 10 mg/L, Sulphide > 2 mg/L, Vanadium, Silica > 60 mg/L. Large amounts of colour and turbidity interfere. Fats, oil, proteins, surfactants and tar.
Kalibracija:	Automatic, 2-point; frequency freely programmable
Kivete:	10 min (dilution + 5 min)
Klasa zaštite:	Protection class: Analyser cabinet: IP44 / Panel PC: IP65
Kvaliteta uzorka:	Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU
Masa:	25 kg
Materijal:	Hinged part: Thermoform ABS, door: PMMA
	Wall section: Galvanised steel, powder coated
Mjerna metoda:	Molybdate blue method (630 nm), conform with APHA 4500-P (C) and ( E)
Mjerni rang:	0.005 - 1 mg/L PO <sub>4</sub> -P
	Optional:
	0.001 - 0.1 mg/L
	0.0025 - 0.25 mg/L
	0.0025 - 0.5 mg/L
	0.04 - 4 mg/L (with internal dilution)
	0.08 - 8 mg/L (with internal dilution)
	0.5 - 100 mg/L (with internal dilution)
Model:	EZ1032
Napajanje:	100 - 240 VAC, 50/60 Hz
	Max. power consumption: 120 VA
Odvod:	Atmospheric pressure, vented, min. Ø 32 mm
Parametar:	Orthophosphate (PO <sub>4</sub> -P)
Pauza:	100 - 240 VAC, 50/60 Hz
Precision:	1% full scale range for standard test
Protok uzorka:	100 - 300 mL/min
Reagent Requirements:	Keep between 10 - 30 °C
Što je u pretincu:	EZ1032 Phosphate Analyser, Instruction Manual, 1 x Double Bit Door key, 1 x Mounting Brackets, 1 x empty 5 Reagent Container with Fittings (for Colour Solution), and 1 x empty 2.5L Glass Reagent Container with Fittings (for Reductor Solution)
Temperatura prostora:	10 - 30 °C ± 4 °C deviation at 5 - 95% relative humidity (non-condensing)
Temperatura uzorka:	5 - 30 °C
Uzorak: tlak:	By external overflow vessel
Validation:	Automatic; frequency freely programmable

---

## Što je u pretincu

EZ1032 Phosphate Analyser, Instruction Manual, 1 x Double Bit Door key, 1 x Mounting Brackets, 1 x empty 5 Reagent Container with Fittings (for Colour Solution), and 1 x empty 2.5L Glass Reagent Container with Fittings (for Reductor Solution)